



CMX1402H

A step up from the CM1401H, with the addition of a mechanical 4WD. A shaft driven cutting platform and Hirosaki blades mean this mower will go places. EXPLORE WHAT YOU ONCE THOUGHT WAS IMPOSSIBLE.



f razorbackbrushcutters

SPECIFICATIONS	
Model	Razorback CMX1402H
Manufacturer	Canycom - Japan
Engine Manufacturer/Model	4WD Honda GX390
Output/Horsepower/RPM	11.7 HP (8.7KW)
Displacement (cc)	389
Torque (Net)	26.5 Nm
Fuel type	Petrol
Fuel Capacity (L)	6.1
Ground Speed (Km/hr)	13.2
Transmission	Continuously variable
Final Drive	Selectable 4WD heavy duty dual range with positive diff lock
Brakes	Enclosed internally expanding automotive style
Steering	Enclosed automotive style rack & pinion
Turning Radius (mm)	1800
Warranty	3 years / 1000 hours
Weight (kg)	340 (fuel tank full)
Overall Dimensions (cm)	1980L x 1020W x 900H
Cutting Height (mm)	0-150
Cutting Width (mm)	975
Blade System	Bolt on swing blades
Drive System	Shaft Drive
Gradeability	25°
Stability	30°

FEATURES

- Dual range transmission for increased pulling and climbing power
- Low centre of gravity for amazing stability on slopes and rough terrain
- No deck belt no more fear of belts breaking!
- Tight turning radius for mowing around trees and other obstacles
- Ultra low seat height creating more stability for hillside mowing
- Diff lock for ultimate traction
- High and low ratio gearbox
- Easy and safe control layout so anyone can operate it
- Unique blade metallurgy
- Tough shaft drive providing maximum torque and reducing maintenance
- Compact mowing width for maneuverability and speed

BUILT TOUCH

www.therazorback.com.au